

DECLARATION OF PERFORMANCE No. M15-20/2018-1

- 1. Unique identification code of the product-type: Category I Calcium Silicate blocks ARKO M-15.
- 2. Intended use/es: unprotected masonry (U) to be used in the construction of walls with thin-layer mortar seams, in single-storey buildings and self-supporting industrial and multi-storey buildings
- **3. Manufacturer:** "Silikatas" AB, Savanorių pr. 124, Vilnius LT-03153, <u>www.silikatas.lt</u>, <u>info@silikatas.lt</u>, <u>phone.</u>+370 5 2311850. **4.** System of assessment and verification of consistency of performance: 2+
- 5. Harmonised standard: LST EN 771-2:2011+A1:2015 "Specification for masonry units-Part 2:Calcium silicate masonry units".
- 6. Notified body: the state enterprise "Statybos produkcijos sertifikavimo centras", Linkmenų g. 28, Vilnius, identification no. 1397.
- 8. Declared performance:

Essential Characteristics	Unit	Performance	Class (group)
Dimensions: length, width, height	mm	340 x 150 x 198	
Dimensional Tolerances Category	mm	±2 x ±2 x ±1	T2
Configuration group according to EC 6 Product displayed with its bed surface pointing up		a de la constante de la consta	1
Compressive Strength:		$^\perp$ to the bed surface of the intact product	
Mean	N/mm ²	≥20,2	
Normalized	N/mm ²	≥20,0	
Shear bond strength, fixed value by LST EN 998-2 (annex C)	N/mm ²	0,3	20
Reaction to fire			A1
Water absorption	%	≤18	
Water vapour diffusion coefficient according to LST EN 1745			
(annex A)		5/25	
Direct airborne sound insulation:			
Gross dry density	kg/m³	1410-1600	1,6
Percentage of void volume	ку/ш %	16	1,0
Total minimum thickness of shells and webs:	70		
Longitudinal, as a percentage of the product's length			
Transversal, as a percentage of the product's width	%	29	
	%	62	
Thermal conductivity $\lambda_{10,dry,unit}$ according to LST EN 1745 (annex B)			
	W/mK	0,68	
Durability against freeze-thaw	Cycles	≥ 50	F2
Dangerous substances		None	
			1

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Nema.

Signed for and on behalf of the manufacturer by:

Vytautas Česnauskas, Director General

Vilnius, 2018-05-02